

ZD220 4-inch Value Desktop Printer

Reliable Operation, Quality Construction, Unsurpassed Value

Not all printers are created equally, especially basic models. To reduce costs, value printers are often constructed using less expensive components. Many fail to perform under more demanding duty cycles, create delays and downtime for repairs, and require replacement after only a few years of use. Instead of conserving budget, customers are left with greater expense and hassle.

Zebra does it differently. The ZD220 desktop printer gives you reliable operation and basic features at an affordable price—both at the point of purchase and across the entire lifecycle. Engineered with Zebra quality, it boasts a dual-wall construction for added durability. And, it is ENERGY STAR® qualified to reduce your operational expenses. Built to last for years, the ZD220 provides an outstanding return on your investment.



Get Printing Quickly

The ZD220 is simple to install and begin printing – right out of the box. USB connectivity allows for universal interoperability. Easily replace legacy printers using ZPL, EPL or non-Zebra command languages. And, media changes are expedited with Zebra's OpenACCESS™ clamshell design. It is ideal for use in transportation and logistics, light manufacturing, retail and healthcare applications to print a variety of tickets, tags, passes, labels and receipts.

Basic Features for Simple Operation

This 4-inch printer produces labels quickly, up to 4" per second, to keep your workflows moving. Increased memory allows you to store more fonts and graphics. A single LED indicator and single button for feed/pause make it easy to operate and identify printer status. Choose from direct thermal or thermal transfer models, and add an optional factory-installed peeler. The ZD220 features a core set of Print DNA software applications, powered by Link-OS® Basic, to deliver a cost-effective and dependable print experience.

Backed by Zebra's Worldwide Service and Support

Access support quickly anywhere around the globe through Zebra's trusted network of more than 10,000 partners. Avoid costly repairs and downtime with an affordable service plan that's tailored to the coverage you need for your desktop printer. Zebra's OneCare SV provides the right level of service at the right price. It gives you two years of coverage for normal wear and tear, double the standard warranty coverage, priority turnaround times at the depot and more—all for a tiny fraction of the cost of a single repair.

Consistently Exceptional Zebra Certified Supplies

Printing supplies can impact everything from printhead lifespan to operational efficiency. That's why we design, produce and rigorously pretest our own line of thermal printing supplies to ensure consistent, optimized performance in your Zebra printer—and peace of mind for you. For industry-leading quality, service and thermal printing expertise, choose Zebra Certified Supplies.

The ZD220 gives you the quality and reliability you expect from Zebra. And, it helps you conserve costs now, and for years to come. Gain your competitive edge with Zebra.

For more information, please visit us on www.barcodes.com.au/zd220t-desktop-printer/ or call us on 1300 800 999



PRODUCT SPEC SHEET

ZD220 VALUE DESKTOP PRINTER

ZD220 Specifications

Standard Features

Thermal Transfer or Direct Thermal print method
 ZPL and EPL programming languages
 Single LED status indicator
 Single button for feed/pause
 USB connectivity
 OpenACCESS™ for easy media loading
 Dual-wall frame construction
 ENERGY STAR qualified

Physical Characteristics

Dimension	Thermal Transfer: 10.5 in. L x 7.75 in. W x 7.5 in. H 267 mm L x 197 mm W x 191 mm H Direct Thermal: 8.6 in. L x 6.9 in. W x 5.9 in. H 220 mm L x 176 mm W x 151 mm H
Weight	2.5 lbs./1.1 kg

Printer Specifications

Resolution*	203 dpi/8 dots per mm
Memory	256 MB Flash; 128 MB SDRAM
Maximum Print Width	4.09 in./104 mm
Maximum Print Speed	4 in./102 mm per second
Media Sensors	<ul style="list-style-type: none"> • Movable black mark sensor, limited range from center to left side • Fixed off-center gap sensor
Firmware	ZPL II; EPL 2; XML

Media and Ribbon Characteristics

Maximum Label Length	39.0 in./991 mm
Media Width	1.00 in. / 25.4 mm to 4.4 in. / 112 mm
Media Roll Size	5.00 in./127 mm outer diameter Core inner diameter: 0.5 in. (12.7 mm) and 1.0 in. (25.4 mm) standard, 1.5 in. (38.1), 2.0 in., (50.8 mm) and 3.0 in. (76.2 mm) using optional adapters
Thickness	0.003 in. (0.08 mm) min.; 0.0075 in. (.1905 mm) max. (tear-off mode only)
Media Types	Roll-fed or fan-fold, die cut or continuous with or without black mark, tag stock, continuous receipt paper, and wristbands
Ribbon Outside Diameter	1.34 in./ 34 mm (74 m)
Maximum Ribbon Length	244 ft. (74 m)
Ribbon Ratio	1:1 media to ribbon (74 m)
Ribbon Width	1.33 in./ 33.8 mm ~ 4.3 in./ 109.2 mm
Ribbon Core I.D.	74 Meter ribbon 0.5 in./ 12.7 mm

ZD220 Specifications

Operating Characteristics

Operating Temp.	40° to 105° F/4.4° to 41° C
Storage Temp.	-40° to 140° F/-40° to 60° C
Operating Humidity	10% to 90% non-condensing
Storage Humidity	5% to 95% non-condensing
Electrical	Auto-detectable (PFC Compliant) 100-240VAC, 50-60Hz; ENERGY STAR qualified

Operations and Accessories

Media Handling	Factory installed peeler
Real Time Clock	None

Fonts/Graphics/Symbologies

Bar Code Ratios	2:1 and 3:1
1D Bar Codes	Code 11, Code 39, Code 93, Code 128, ISBT-128, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2-or 5-digit extensions, Plessey, Postnet, Standard 2-of-5, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Codabar and Planet Code
2D Bar Codes	Codablock, PDF417, Code 49, DataMatrix, MaxiCode, QR Code, MicroPDF, Aztec
Fonts and Graphics	16 resident expandable ZPL II bitmap fonts Two resident scalable ZPL fonts Five resident expandable EPL2 fonts Native open-type font support Unicode compliant for multi-language, on demand thermal printing China units include SimSun simplified Chinese font 50 MB user available non-volatile memory, 8 MB user available SDRAM

Printers Supplies

Keep your Zebra printer up and running with genuine Zebra printer supplies, available directly from Zebra.

Regulatory

- IEC 60950-1, EN55022 Class B, EN55024, EN61000-3-2, EN61000-3-3, FCC Class B, ICES-003, FCC 15.209; 15.247(d), IC RSS 247, EN 300 328, EN 301 893, EN 62311, cTUVus
- CE Marking, VCCI, C-Tick, S-Mark, CCC, CU, BSMI, KCC, SABS, IN-Metro, BIS, NOM

Recommended Services

Zebra OneCare SV

Print DNA Software

This printer is supported by a core set of PrintDNA applications powered by Link-OS® Basic.

Print DNA features may vary by model and a Support Contract may be required. For more information, please visit www.zebra.com/printdna

For more information, please visit us on www.barcodes.com.au/zd220t-desktop-printer/ or call us on 1300 800 999



Asia-Pacific Headquarters
+65 6858 0722
contact.apac@zebra.com



Phone: 1300 800 999
Email: sales@barcodes.com.au
Website: www.barcodes.com.au