

SELPHY QX20

COMPACT PHOTO PRINTER

TECHNICAL SPECIFICATIONS



Canon

SELPHY QX20

COMPACT PHOTO PRINTER

Bring colour to your everyday



Two paper sizes in one printer

Simply change the paper to choose between card-size and square format. Expand the creative possibilities with bordered and borderless for each.



Clearer and more vivid

Print images from your phone faithfully as you imagined them, with smooth gradations, beautiful color reproduction for skin tones, and vivid colors.



Beauty that lasts 100-years

A special protective overcoat is applied to cover the photo after the printing process. This protects your important prints against water and dirt and prevents color bleeding and fading.



Easy connection to your smartphone

Simply download the free SELPHY Photo Layout 4.0 app, connect your phone to your printer via Wi-Fi and follow the instructions. Alternatively, scanning the QR code on the printer itself will easily connect your printer to your smartphone.



Canon

SELPHY QX20 | SPECIFICATIONS

COMPACT PHOTO PRINTER

Printer Functions	
Printing method	Dye-sublimation thermal transfer
Album storage	100 years supported
Print resolution	287 x 287 dpi
Gradation	256 shades per colour
Printer speed* ¹	Approx. 40 sec.
Number of printable sheets* ²	Approx. 20 sheets
Paper feed capacity	10 sheets
Dimensions and weight	
Dimensions (WxHxD)* ³	Approx. 102.2 x 32.9 x 145.8 mm
Weight* ⁴	Approx. 455g
Power source	
Printing while charging	Not supported
Battery Type	Built-in Lithium-ion battery
Nominal voltage (DC)	7.4 V
Nominal capacity	850 mAh
Battery rated input (voltage)	DC 0.5 V ± 0.5 V
Battery rated input (current)	Max 1.5A
Charging time* ⁵	Approx. 1 hr 20 min
Charging cable terminal	USB Type-C
External Interface	
Wi-Fi spec & frequency	2.4GHz. IEEE802.11 b/g compliant.
Wi-Fi security	WPA3-Personal Transition Mode
Connection method	Direct connection – SELPHY Photo Layout app 4.0 or later
Simultaneous connections	6 devices
Other	Memory card – not supported Communication via USB cable – not supported
Consumables	XS-20L, XC-20L, XC-60L

Variations



Black

Red

White

*1 Measurement conditions: Room temperature (23°C/73°F), from start of printing until paper ejection is finished.

*2 Measurement conditions: Room temperature (23°C/73°F), using a new, fully charged battery, based on Canon testing standards.

*3 Excluding the projecting parts

*4 Excluding the colour ink cassette and labels

*5 At room temperature. May take approx. 4 hours if the battery is fully discharged, such as when initially charged or after extended storage.

Canon

**www.canon.com.au
www.canon.co.nz**