



TJ-4420TN

Titan Industrial
Label Printer

www.brother.com.au



Food &
Beverage



Manufacturing
& Transport



Warehousing
& Logistics



Retail

TJ-4420TN

Titan Industrial Label Printer



Key features:

- Simple, robust and reliable direct thermal and thermal transfer technology
- Print more than 10,000 labels a day
- 203dpi print resolution
- Max. 356mm/sec print speed
- 8.3cm colour LCD
- High-capacity 600m ribbon for fewer changes
- Supports Software Development Kits (SDK's) and printer command languages, including ZPL2 emulation
- USB, Serial, 10/100Base-TX Wired LAN and WLAN connectivity
- Optional peeler, cutter and dual Wi-Fi and Bluetooth accessories



Drop-in, connect and print

The TJ-4420TN is ready to meet the demands of your business. Its intelligent design allows you to simply drop-in, connect and print, delivering stress-free and seamless integration, without compromising productivity



Compatible with your existing infrastructure

Take advantage of the suite of connectivity options including USB 2.0, serial, Ethernet, and optional dual Wi-Fi and Bluetooth accessories, and its ability to support Software Development Kits (SDK's) and various printer command languages, including ZPL2 emulation



A solution built for your business

The optional peeler, cutter, and dual Wi-Fi and Bluetooth accessories allow you to create a tailor-made solution that meets the demands of your business



Reliable, built-in technology

Whether you're printing shipping and receiving labels or product and compliance labels (and anything else in between!), using thermal technology delivers a simple, robust and reliable label printing solution. Accompanied by a high-capacity 600m ribbon and crisp 203dpi outputs, the TJ-4420TN works hard to deliver professional quality labels on an industrial scale



Warranty you can count on

A generous 2-year warranty on hardware and print heads means these mission-critical machines will always be performing at their best



At your side support

Wherever you are in Australia, Brother offers free product support for the lifetime of your product

Technical Specifications for the TJ-4420TN

General

Print Technology	Direct Thermal / Thermal Transfer
Print Resolution	203dpi
Maximum Print Speed	356 mm / second
Maximum Print Width	104mm
Maximum Print Length	25,400 mm
Minimum Print Length	Continuous: 5mm Tear mode: 50 mm Peeler mode: 12.7mm Cutter mode: 25.4mm
Emulation	FBPL-EZD (TSPL2, EPL2, ZPL2, DPL)
Feed	Yes

Interface

USB	Standard: USB Ver.2.0 (Full Speed) (Type B)
Serial	Standard: RS232C (DB9 male)
Wired LAN	Standard: 10/100BASE-TX
USB Host Ports	USB Type-A Class ID: HID USB mass-storage device class USB Regulation: 2.0
Bluetooth Profile	PA-WB-001 (Optional): Bluetooth Ver.5.0, SPP (Bluetooth Classic), GATT (Bluetooth Low Energy)
Wi-Fi	PA-WB-001 (Optional): IEEE 802.11 a/b/g/n (a band is 5GHz; b/g/n is 2.4GHz)
WLAN Security	Compliant to IEEE 802.11 a/b/g/n with dual band support Supports Bandwidth in 5GHz 20/40 MHz 802.11n Features: 802.11n HT20 Roaming without data lost in AP cover rage Protocols: IPv4, ARP, ICMP, UDP, TCP, RAW, DHCP Client, DHCP FQDN Option, Unicast DHCP Offer

Memory

Standard Memory	RAM: 256MB Flash: 512MB (MicroSD Flash memory card reader or Flash memory expansion, up to 32 GB)
-----------------	--

Power Supply

Adapter	Internal Supply: 100 - 240 V 50/60Hz Output: 24V/3.75A. 90W
---------	--

Media Specification

Types	Generic thermal continuous, black mark, die cut label with gap, fan-fold, notch media, perforated, tag, care label
Wound Type	Outside Wound
Roll Size	Tear Mode: 50mm to Max Print Length Peeler Mode: 12.7mm - 152.4mm Length Cutter Mode: 25.4mm - 2,286mm Length Max Roll Diameter: 203.2mm Core size: 38.1mm - 76.2mm Tear / Peeler Mode: 20mm - 120mm Width Cutter Mode: 20mm - 114mm Width
Roll Width	20mm - 114mm

Ribbon Specification

Types	Wax, Resin, Semi (Wax/Resin)
Wound Type	Inside or Outside Wound
Ribbon Width	20mm - 114mm (0.79 inch to 4.5 inch)
Ribbon Length	600m

Software

Software Included	Windows: BarTender Ultra Lite Edition, BPM (Brother Printer Management Tool), CommTool (Brother Communication Tool), Printer Driver Mac: Printer Driver Linux: Printer Driver
Windows Printer Driver	Windows 11 Windows 10 Windows 8.1 Windows 7 Server 2012 Server 2012R2 Server 2016 Server 2019
MAC Printer Driver	macOS X 10.11.x macOS 10.12 - 12.0

Software	
Linux Printer Driver	Linux Ubuntu V11.04-16.04 Fedora 24 SUSE Linux Enterprise Server 12 CentOS Linux 7.2 Red Hat Enterprise 7.3
Mobile Software Development Kits (SDK's)	Android V5 iOS V9
Windows SDK	Server 2019 Windows 10 and Server 2016 Windows 8.1 and Server 2012 R2 Windows 8 and Server 2012 Windows 7
Android SDK	V5-V10
iOS SDK	V9-V13.2
Supported Command	FBPL-EZD (EPL,ZPL,ZPL2,DPL)
SAP Device Type	SAP_BASIS Release 6.20 - 7.11, except 7.10
Bar Code Symbologies	Linear: Code128UCC, Code128 subsets A,B,C, EAN128, Interleaved 2 of 5, Interleaved 2 of 5 with check digit, Standard 2 of 5, Insuatrial 2 of 5, Code39, Code39 with check digit, Code93, EAN13, EAN8, UPCA, UPCE, EAN and UPC 2 (5) digits add-on, Codabar, Postnet, MSI, MSI with check digit, PLESSEY, China post, ITF14, EAN13, Code11, TELEPEN, TELEPENN, PLANET, Code49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS 2-dimensional: CODABLOCK F mode, GS1 DataBar, GS1 DataMatrix, Maxicode, AZTEC, PDF417, QR Code, Micro PDF 417, TLC39
Fonts	8 alpha-numeric bitmap fonts for FBPL Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font
Dimensions and Weight	
Weight	15.35kg (without roll)
Dimensions	276mm x 502mm x 326mm (W x D x H)
Control Panel	LCD display, 1 status indicator and 6 button navigation
Environment	
Operating Temperature	0 - 40°C
Operating Humidity	25 - 85% non-condensing
Storage Temperature	-40 - 60 °C
Storage Humidity	10 - 90% non-condensing
Printer Safety	EMC / RMC
Warranty	
Hardware	2 Year Return to Base
Print Head	2 Year Return To Base (25km or 6 months on print head)
Package Contents	
Package Contents	Printer, Quick Start Guide, USB cable, Power Cord, Product Safety Guide, Paper Core
Optional Accessories	
Dual Bluetooth & Wi-Fi	PA-WB-001
Peeler	PA-LP-006
Cutter	PA-CU-005



Working with you for a better environment

At Brother, our green initiative is simple. We strive to take responsibility, act respectfully and try to make a positive difference to help build a society where sustainable development can be achieved. We call this approach Brother Earth.



All specifications correct at the time of printing and are subject to change. Brother is a registered trademark of Brother Industries Ltd. Brand product names are registered trademarks or trademarks of their respective companies.

Brother Empowers



Brother Corporate Solutions



Brother International Australia



BrotherAU

brother
at your side