

SELPHY QX20

COMPACT PHOTO PRINTER

TECHNICAL SPECIFICATIONS



Canon

SELPHY QX20

COMPACT PHOTO PRINTER

Bring colour to your everyday



TWO PAPER SIZES IN ONE PRINTER

Simply change the paper to choose between card-size and square format. Expand the creative possibilities with bordered and borderless for each.



CLEARER AND MORE VIVID

Print images from your phone faithfully as you imagined them, with smooth gradations, beautiful color reproduction for skin tones, and vivid colors.



BEAUTY THAT LASTS 100-YEARS

A special protective overcoat is applied to cover the photo after the printing process. This protects your important prints against water and dirt and prevents color bleeding and fading.



EASY CONNECTION TO YOUR SMARTPHONE

Simply download the free SELPHY Photo Layout 4.0 app, connect your phone to your printer via Wi-Fi and follow the instructions. Alternatively, scanning the QR code on the printer itself will easily connect your printer to your smartphone.



Canon

SELPHY QX20 | SPECIFICATIONS

COMPACT PHOTO PRINTER

| PRINTER FUNCTIONS | |
|--|--|
| Printing method | Dye-sublimation thermal transfer |
| Album storage | 100 years supported |
| Print resolution | 287 x 287 dpi |
| Gradation | 256 shades per colour |
| Printer speed* ¹ | Approx. 40 sec. |
| Number of printable sheets* ² | Approx. 20 sheets |
| Paper feed capacity | 10 sheets |
| DIMENSIONS AND WEIGHT | |
| Dimensions (WxHxD)* ³ | Approx. 102.2 x 32.9 x 145.8 mm |
| Weight* ⁴ | Approx. 455g |
| POWER SOURCE | |
| Printing while charging | Not supported |
| Battery Type | Built-in Lithium-ion battery |
| Nominal voltage (DC) | 7.4 V |
| Nominal capacity | 850 mAh |
| Battery rated input (voltage) | DC 0.5 V ± 0.5 V |
| Battery rated input (current) | Max 1.5A |
| Charging time* ⁵ | Approx. 1 hr 20 min |
| Charging cable terminal | USB Type-C |
| EXTERNAL INTERFACE | |
| Wi-Fi spec & frequency | 2.4GHz. IEEE802.11 b/g compliant. |
| Wi-Fi security | WPA3-Personal Transition Mode |
| Connection method | Direct connection – SELPHY Photo Layout app 4.0 or later |
| Simultaneous connections | 6 devices |
| Other | Memory card – not supported Communication via USB cable – not supported |
| Consumables | XS-20L, XC-20L, XC-60L |

VARIATIONS



BLACK

RED

WHITE

*1 Measurement conditions: Room temperature (23°C/73°F), from start of printing until paper ejection is finished.

*2 Measurement conditions: Room temperature (23°C/73°F), using a new, fully charged battery, based on Canon testing standards.

*3 Excluding the projecting parts

*4 Excluding the colour ink cassette and labels

*5 At room temperature. May take approx. 4 hours if the battery is fully discharged, such as when initially charged or after extended storage.

Canon

**www.canon.com.au
www.canon.co.nz**